

# DEPARTMENT OF PURCHASING & SUPPLY MANAGEMENT

12000 Government Center Parkway, Suite 427 Fairfax, Virginia 22035-0013

www.co.fairfax.va.us/dpsm

T R G I N I A

Telephone: (703) 324-3201 Fax: (703) 324-3228 TTY 1-800-828-1140

AMENDMENT NO. 1

MAR 1 2 2003

SUBJECT:

Large Kitchen Equipment

CONTRACTOR

**VENDOR CODE** 

CONTRACT NO.

Calico Industries

B13555193901

RQ02-563852-24C

P.O. Box 2005 Annapolis Junction, MD 20701-2005

By mutual agreement, Contract RQ02-563852-24C is amended to reflect the addition of the following items as line item 22 through 24.

Item No.

Description

Qty. Unit Unit Price

Extension

Price

22. Utility Cart

3 Ea \$ 309.24

s 927.72

STANDARD: Metro MW108. or equal

**DESCRIPTION:** Stainless Steel utility cart w/2 stainless steel solid shelves and <u>one handle</u>.

MATERIAL: Stainless steel posts and shelves. Donut bumpers on wheels.

SHELVES: Two shelves

CAPACITY/SIZE: 24" x 36" x 40".

COLOR: Stainless Steel

ELECTRICAL: None.
PLUMBING: None.

APPROVAL AND LABELS REQUIRED:

NSF.

WARRANTY: One year on labor and parts.

ACCESSORIES:

Encircling rubber bumpers.

Only one handle.

3. 5" light duty casters (375 pound load capacity).

Delivery 30 days after receipt of order

## Description

**Unit Price** Qty. Unit

2

**Fxtension** Price \$ 7554.00 \$ 15, 10800

r.01/13

#### 3587-011-006--DOUBLE CONVECTION OVEN, 23. ELECTRIC

STANDARD: Blodgett Model Mark V-Double, or equal.

DESCRIPTION: Double-deck electric all-purpose convection oven, to have two independent porcelain zed steel oven cavities, with lights in each cavity.

EXTERIOR: Full angle iron frame. Top, front and sides to be heavy gauge stainless steel. Oven front to be stainless steel.

INTERIOR: Double sided porcelain zed steel liner baking compartment.

LEGS: Adjustable 6" stainless steel legs.

DOORS: Dependent stainless steel doors with simultaneous door operation. Porcelain door handle. Dual pane thermal glass windows. Safety switch that turns off fan when doors are opened. Seal must be stainless steel.

INSULATION: High density K-Fac insulation.

SHELVES: Five (5) removable chrome-plated racks per oven chamber, eleven positions on guide in each oven chamber with minimum of 1-5/8" spacing.

FANS: To be powered by 1/3 motor that is serviceable from the front and has two-speed fan.

CAPACITY/SIZE: Oven shall accept five 18" x 26" pans in left to right position.

FLOOR SPACE: 38 1/2" wide, 36 7/8" deep, 65" high.

COLOR: Top, sides, and door stainless steel.

ELECTRICAL: 480 volts; 60 cycles; 14/13/13 amps; three phase; 1/3 to ½ HP. 11KW/single/22KW/double; 60 Hz; 3 phase; 11 KW/single/22KW/double; 31/29/29 amps. UL listed or equal.

# APPROVAL AND LABELS REQUIRED: NSF

#### ACCESSORIES:

- Two-speed motor.
- Solid state timer and controls.
- Calibration of temperature gauge on 3. location.
- Two user's manuals.
- Electric timer with buzzer.
- Minimum one oven light per cavity.

WARRANTY: Two years, including labor and parts, five year limited oven door warranty.

SERVICE: Must be service representative in Metropolitan Washington area.

\_ days after receipt of order. Delivery

Extension

# 24. CONVECTION OVEN, NATURAL GAS

STANDARD: Blodgett DFG-100 Double or equal

DESCRIPTION: Double-deck gas all-purpose convection oven, to have two independent porcelain zed oven cavities, with lights in each cavity.

**EXTERIOR:** Full angle-iron frame. Top, front and sides to be heavy gauge stainless steel. Oven doors to be stainless steel.

INTERIOR: Porcelainzed interior.

LEGS: Adjustable 6" stainless steel legs.

DOORS: Dependent stainless steel doors with simultaneous door operation. Porcelain door handle. Dual pane thermal glass windows. Safety switch that turns off fan when doors are opened.

INSULATION: High density insulation.

SHELVES: Five (5) removable chrome-plated steel racks per oven chamber, eleven positions on guide in each oven chamber.

FANS: To be powered by 1/3 hp motor that is serviceable from the front.

CAPACITY/SIZE: Oven shall accept five 18" x 26" pans in right to left or font to back position.

FLOOR SPACE: 38 1/4" wide, 38 9/16" deep, 86 1/4" high.

COLOR: Top, sides, and door stainless steel.

ELECTRICAL: 3-wire, 6 amp, 115 VAC; 1 phase, 60Hz, 1/3 HP, 2 speed motor, 1140 and 1725 RPM, 120,000 BTU's/hr (60,000 each section).

GAS; 3/4 inch gas inlet, N.P.T.

APPROVAL AND LABELS REQUIRED: NSF and AGA

### ACCESSORIES:

- Two-speed motor-60 Hz
  single phase
- single phase.
  2. Solid state timer and controls.
- Calibration of temperature gauge on location.
- Two user's manuals.

**WARRANTY**: One year, including labor and parts, five year limited warranty on oven doors.

SERVICE: Must be service representative in Metropolitan Washington area.

Delivery 30 days from receipt of order.

All other prices, discounts, terms, and conditions remain the same.

Cathy A. Muse, CPPO

Director/County Purchasing Agent

ACCEPTANCE:

BY. Tatre Laborers

Printed

Director, Large Caup Dept.

2-24-03

Date

DISTRIBUTION:
Assistant Buyer – Mable McCarthy
Assistant Buyer – Van Fuller
Contract Administrator
Contractor(s)
Office of Sheriff – Diane Wilt

FCPS/Food and Nutrition Services -- Ruth Matoto Maria Adair Facilities Management Division -- Elyce Rollins Adult Detention Center -- Torn Kennedy